

DECORE PLASTERS

USE DECORE PLASTER

TO SAVE 50-60% COST ON CEMENT & LIME PLASTER



STUCCO DECORE H100 100% Sand, Cement & Lime

FREE

For more
Technical specifications
and Quality Certifications
issued by World renowned
Certification bodies

Visit: kandyhardware.lk



Sales & Marketing: Gypcore Concepts Centre

108, Maya Avenue Colombo – 06

Phone: 011-2556699 / 0773 051 366

Email : gypcore@sltnet.lk Web: www.kandyhardware.lk

🗨 www.kandyhardware.lk

STUCCO DECORE PLASTERS

Use it & feel the smoothest difference. **DECORE** PLASTERS



PRODUCT FACTS

DECORE plasters are the optimal choice for:

- Residential buildings
- **Apartment Complexes**
- Hotels
- Commercial buildings
- Offices

STUCCO DECORE

Technical Specifications:

Water/ Plaster ratio: 70:75% Initial setting time: 7-12min Flexural strength > 3N / mm2 Density: 700kg/m3 Packaging: 25 kg PP bags

WHY DECORE PLASTERS are so good?

- DECORE PLASTERS produced in Oman are made with natural high - purity Gypsum.
- DECORE PLASTERS deliver a superb white smooth finish enhanced with high performance polymers.
- DECORE PLASTERS are sophisticated, simple and different.
- Whether you want it hand applied, machine applied, finishing plaster or one coat plaster, DECORE PLASTER range has it all.

General Features:

- High purity
- High Smoothness
- Consistent performance

COMPARISON CHART

Sand, Cement, Lime Plaster \MR DECORE Plaster

Price & demand of SAND is increasing rapidly, due to mining & transport restrictions imposed by the Government as an environmental protection measure.

> Quality and Size of SAND cannot be controlled as it is full of impurities.

SAND PLASTER NEEDS CEMENT, SAND & LIME with water. Mixing is handled by Labour without any standardized ratio.

> Hairline cracks are always found in a SAND CEMENT PLASTER.







SAND CEMENT PLASTER needs water curing for 8-10 days at least 2 times a day.

After application of SAND CEMENT PLASTER a coat of PUTTY is required to smoothen the surface for painting.

DECORE PLASTER powder is freely available and transportable without any restrictions.

DECORE PLASTER is a waste free, high quality, lab tested & factory made product.

DECORE PLASTER is a readymade powder to be mixed ONLY with a specified proportionate of WATER.

No hairline cracks will occur after application of DECORE PLASTER

- DECORE PLASTER is calcium sulphate with two molecule of water of crystallization.
- (CaSO4.2H2O) contains nearly 21% water and 79% calcium sulphate.
- DECORE PLASTER sets on its own, without curing

DECORE PLASTER requires NO CURING, hence, NO WASTAGE OF WATER.

DECORE PLASTER is a ONE SHOT PROCESS which is ready for painting immediately after drying.

DECORE PLASTERING CAN BE APPLIED ON

- RED BRICKS
- CEMENT BLOCKS
- CONCRETE WALL & CELLING
- AAC BLOCK
- FLYASH BRICKS

KEY FEATURES

- BONDING PERFORMANCE
- LONG LIFE
- NON-TOXIC & ANTI FUNGUS
- LOW THERMAL CONDUCTIVITY
- NO CURING REQUIRED
- EASY APPLICATION
- FLEXURAL TENSILE STRENGTH

ADVANTAGES OF DECORE PLASTERS

- DECORE PLASTER is directly applied on Brick, Block or RCC, hence no putty finishing is required.
- DECORE PLASTER requires no curina. therefore it is ready to be painted.
- DECORE PLASTER saves time during construction.
- DECORE PLASTER on drving out, it forms a sufficient dense to resist normal knocks.
- DECORE PLASTER is comparatively easy to spread and level.
- DECORE PLASTER reduces the Consumption of paint up to 30%.
- DECORE PLASTER has no appreciable chemical action on paint.
- DECORE PLASTER could be applied and finished to a minimum thickness to cover maximum area.
- DECORE PLASTER is perfectly lined, leveled with sharp corners giving a smooth surface.
- DECORE PLASTER Saves electricity used by Air Conditioners due to it's low thermal conductivity.
- DECORE PLASTER is a 100% Eco-friendly product.
- DECORE PLASTER is light in weight and reduces load in structure

OUR BRAND PORTFOLIO





DECORE

GYPCORE

FUSION

Manufacturer: Global Gypsum Board Co. LLC., Sultanate of Oman



Sole Distributor for Sri Lanka:



KANDY HARDWARE (PVT) LTD.

Jo.359, D.S.Senanayake Vidiya, Kandy, Sri Lanka Tel / Fax : 081-2222598 Email: kandyhardware@sltnet.lk,



Gypcore Concepts Centre

Tel: 0112 55 66 99 / +94 773 051 366

Web: www.kandyhardware.lk Email: gypcore@sltnet.lk